




INFORMATION
SECURITY

INTIMUS 120 IN THE DEPARTMENT

- ▶ Low noise level
- ▶ Integrated Auto Reverse Function for easy removal of paper jams
- ▶ Illuminated indicators for stand-by, basket full, door open and paper jam
- ▶ Sealed dust-free design with robust wooden cabinet
- ▶ Mounted on rollers for flexible use



EcoLogic

i-control®

DLS

2x2



– a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.

**PROFESSIONAL
DATA SHREDDERS**

SPECIFICATION				
Model	120 SP2	120 SP2	120 CP4	120 CP5
Shred size	5,8 mm	3,8 mm	3,8 x 36 mm	1,9 x 15 mm
Bin size	120	120	120	120
Suitable for	5+	5+	5+	5+
Security level (DIN 66 399)	P-2 / O-1 / T-2 ⁺	P-2 / O-1 / T-2 ⁺	P-4 / F-1 / O-1 / T-2 ⁺	P-5 / F-2 / O-1 / T-2 ⁺
Shredding capacity*	35-38 (sheets) 70 g/m ²	31-33 (sheets) 70 g/m ²	26-28 (sheets) 70 g/m ²	15-17 (sheets) 70 g/m ²
	33-36 (sheets) 80 g/m ²	29-31 (sheets) 80 g/m ²	23-25 (sheets) 80 g/m ²	13-15 (sheets) 80 g/m ²
Cutting speed	100 mm/s	100 mm/s	100 mm/s	100 mm/s
Throughput** (sheets/min)	768 (sheets/min) 70 g/m ²	667 (sheets/min) 70 g/m ²	505 (sheets/min) 70 g/m ²	343 (sheets/min) 70 g/m ²
	727 (sheets/min) 80 g/m ²	627 (sheets/min) 80 g/m ²	465 (sheets/min) 80 g/m ²	303 (sheets/min) 80 g/m ²
Also shreds***				
Dimensions (W/D/H)	54 x 40 x 98 cm	54 x 40 x 98 cm	54 x 40 x 98 cm	54 x 40 x 98 cm

*only floppy disks & ID cards

* based on 70 g/m² A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

** theoretical average performance paper/min

*** in 8 mm strips

HIGH SECURITY SHREDDER

SPECIFICATION		
Model	120 CP6	120 CP7
Shred size	0,8 x 12 mm	0,8 x 4,5 mm
Bin size	120	120
Suitable for	5+	5+
Security level (DIN 66 399)	P-6 / F-3/ T-6	P-7 ⁺ / F-3
Shredding capacity*	10-12 (sheets) 70 g/m ²	7-8 (sheets) 70 g/m ²
	8-10 (sheets) 80 g/m ²	6-7 (sheets) 80 g/m ²
Cutting speed	100 mm/s	100 mm/s
Throughput** (sheets/min)	242 (sheets/min) 70 g/m ²	161 (sheets/min) 70 g/m ²
	202 (sheets/min) 80 g/m ²	141 (sheets/min) 80 g/m ²
Dimensions (W/D/H)	54 x 40 x 98 cm	54 x 40 x 98 cm

*NSA approved (NSA / CSS EPL 02/01)

* based on 70 g/m² A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

** theoretical average performance paper/min